

Integrity Tile

LUXURY VINYL TILE



World of Flooring's Integrity Tile is a waterproof, durable, and pet friendly composite core vinyl tile designed with the customers best interest in mind. Backed by a lifetime residential warranty and an 10 year commercial warranty, the Integrity Tile is an innovative product that's made to last. Choose from World of Flooring's variety of unique skus. From delicate white tiles to striking deep great, the Integrity Tile is sure to leave a lasting impression.



by **SCS**certified.

Integrity Tile



Benefits





Integrity Tile

Application

Perfect for any room, any level; residential and commercial alike.

- Kitchens
- Bedrooms
- Laundry Rooms
- Basements
- Foyers
- Offices
- Bathrooms
- Living Rooms

Installation Method

Swift Click / Floating Click

Warranty

Lifetime Residential Warranty
10 Year Commercial Warranty

Product Information for Integrity Tile

Tile Size.....	12.05" X 24.09"
Thickness.....	5 mm
Wear Layer.....	22 mil Commercial
Pieces per Carton.....	8 pieces
Square Footage per Carton.....	16.13 sf
Cartons per Pallet.....	56 Cartons
Square Footage per Pallet.....	903.06 sf
Edge Description.....	Micro Bevel
Finish.....	Sand Emboss

Features & Benefits

- Unique installation design possibilities
- Quiet floors with superior noise performance
- IIC 67 / STC 64 with underlay
- IIC 62 / STC 63 without underlay
- Waterproof
- Fast and easy installation
- Made from 60% recyclable material
- No pattern repeat
- Withstands temperature range of 45°F - 115°F
- Kid & pet friendly
- Scratch resistant
- Unmatched in-home softness & warmth
- Worry-free maintenance
- Used for heavy residential & light commercial applications



Integrity Tile

PRODUCT SPECIFICATION SHEET

Style Name	Integrity Tile
Product Category	Luxury Vinyl Plank
Wear Layer Finish	Sand Emboss
Wear Layer Thickness	22 mil
Overall Thickness	5mm
Installation	Swift Lock / Floating

TESTING

Otho Phthalate Free	
Reclaimable	
Critical Radiant Flux ASTM E648	Class 1
Impact Sound Conduction/ASTM E492-09	IIC 62db
Dimensional Stability / ASTM F2199	Passes
Resistance to Heat / ASTM F 1514	DELTA E < 8.0 Passes
Resistance to Light / ASTM 1515	DELTA E < 8.0 Passes
Chemical Resistance/ ASTM F925	Passes
Smoke Density / ASTM E662	Under 450
Static Load / ASTM F970	Passes ≤ 1200 lbs
Abrasion Resistance / ASTM D4060	38,000 Cycles
Rolling Loads / ASTM F2753	Passes

WARRANTY

Lifetime Residential
10 Year Commercial

ENVIRONMENTAL

Indoor Air Quality

FloorScore© certified

BETTER PRODUCT

BETTER VALUE

BETTER SOLUTIONS